

ECOPACK L-Type Sealing

AUTOMATIC L-TYPE SEALING MACHINE SERIES

Automatic L-type sealer:

The machine can be added to an existing conveyor line or used by manually feeding the box/package onto the conveyor. Center fold POF/PVC film is used to automatically dispense, wrap and seal over your desired product.. The operator manually sets the sealing length for the product to be wrapped. The sealer has a safety system which immediately stops the sealing mechanism in the event the operators hand or object interferes with the sealing operation. The sealing mechanism has a non stick coating which results in a smoke free operation. All excess plastic is wound onto a dispenser below the machine which can easily be dispensed of. Once the product is sealed it then automatically runs through the thermal shrink tunnel where the the shrink film is heat shrunk tightly around product.




Automatic L sealer & Shrink tunnel



Automatic Side Sealer & Shrink tunnel

Automatic side sealer:

The machine operates similarly as the above. The difference being that on this machine the boxes/product can be of random lengths.



Specification

Model	AST54	AST545	AST518	AST528
Max packing size (mm)	L450×W350×H100	W450×H200	L∞, W+2H≤450, H≤150	W450×H200
Max sealing size (mm)	L550×W450	/	W450	/
Power (KW)	1.3 0	8.50	1.40	12
Capacity	0-20 pcs/min	0-15 pcs/min	0-21 pcs/min	0-15 pcs/min
Voltage	220V 50/60Hz	380V 50/60Hz	220V 50/60Hz	380V 50/60Hz
Sealing temperature	160°C–240°C depends on thickness of film and environment temperature			
Thickness of film (mm)	0.015-0.10			
Air pressure (Kg/cm ²)	5			
Packing material	POF PVC			
Machine weight (kg)	320	210	340	360
Machine size (L×W×H) mm	1700×900×1400	1700×900×1400	1700×1000×1500	1700×750×1500